

The power to go beyond.


Diesel Engine Driven Generators and Welders
for the European Market



Denyo : Making a Difference on Worksites

Worldwide

We use electricity every day, taking it for granted. However, there are a surprising number of situations in which electricity supplied by the power company cannot be used or when there is not enough electricity, such as on construction sites, during disasters, and in developing countries. At such times, we supply as much electricity as is needed, whenever and wherever. And we meet the expectations of customers around the world. Taking this as its mission, Denyo has been working to develop better products ever since its foundation.




Contents

Denyo's Strengths	02
Product Information	04
Engine-Driven Generators	05
Engine-Driven Welder	10
Global Network	12
Corporate Information	12



Denyo's Strengths

01




Boasting a high share of the Japanese market,

Denyo is a leading company in outdoor power sources

Since its establishment in 1948, Denyo has firmly created its own technology, including the release of high-performance, engine-driven generators featuring excellent energy savings and the commercialization of Japan's first small, lightweight engine-driven welders, and has launched a succession of products specialized for use in outdoor locations without sources of power. As a result, today Denyo has grown into a leading company in outdoor power sources, with a market share of 70% in Japan for engine-driven generators, our main product, and 55% of the market for engine-driven welders.

02



Quality products that come from thorough start-to-inish production from design to product inishing

One reason we can create such high-quality products is our thoroughly integrated production of everything besides the engines, from design and manufacture of machine parts to assembly and finishing. Integrated production also enables us to provide products that truly meet customers' individual needs by rapidly manufacturing made-to-order products.

We carefully manufacture generator coils from a single wire.



Winding of copper wire to the rotor by automatic winding machine



Varnishing of rotors for protection against earthquakes, corrosion and harmful substances

03

150 Countries

Our products are used in 150 countries worldwide.

Featuring excellent reliability and durability, high sound insulation, and supplying quality electricity, Denyo's generators are used not only as power sources on construction sites but also as precious sources of power for daily life in developing countries and sparsely populated deserts, isolated islands, and mountainous areas not reached by electricity. They are also used as power sources for events and as backup power sources in times of disaster and power outages. Thus far, our generators have helped people throughout the world, having been selected in important situations, for example, by customers as the power source for Singapore's Independence Day ceremonies and for temporary power supply at a vaccination site in USA.



04



We develop environmentally friendly products.

In recent years environmental regulations have become increasingly strict, as countries around the world have become concerned about air pollution and the effects on human health caused by the gases emitted from automobiles and construction machinery. Denyo was quick to work on improving environmental performance and has assembled a line of environmentally friendly engine-driven generators, including the DCA-US Series (Ultra Silent Series), in which we achieved a low noise level on a par with a quiet office.

HIGH-PERFORMANCE

The Denyo generating system guarantees the following levels of performance:

TEMPERATURE RISE

100 temperature rise at 40 ambient (JEC2130).

INSULATION

Class F (JEC2130).

VOLTAGE REGULATION

Within±0.5% (except DA-6100SSEK5)

FREQUENCY REGULATION

Within 5.0% through no-load to full-load.

VOLTAGE WAVEFORM

Deviation Factor of open-circuit terminal voltage does not exceed 0.06.

ELECTROMAGNETIC INTERFERENCE LEVEL

Attenuated to meet most commercial requirements.

INSULATION RESISTANCE

Higher than 3 Mega-ohms, measured between armature windings and earth, field windings and earth, field control circuit and earth.


- The innovative excitation system* fitted on all models, in conjunction with the AVR and advanced brushless generator, provides fast voltage regulation in response to load variations, enabling use soon after start up. This system provides output stability during load variations.

*U.S.Patent No.4268788


- Synchronous brushless alternator for minimal wear.
- Designed to function in all climatic

Control Panel with Outstanding Usability

Denyo's generators feature a functional panel layout that can be easily operated even by first-timers.



- ① MANUAL & AUTO – START GENERATOR CONTROLLER (DSE6110MK II)
- ② CONTROL POWER SWITCH
- ③ VOLTAGE REGULATOR
- ④ Circuit Breaker (For main)
- ⑤ EARTH LEAKAGE RELAY
- ⑥ CIRCUIT BREAKER (For 3-Phase Receptacle 30A)
- ⑦ CIRCUIT BREAKER (For 3-Phase Receptacle 15A)
- ⑧ CIRCUIT BREAKER (For 1-Phase Receptacle 16A)
- ⑨ 1-PHASE RECEPTACLE (16A)
- ⑩ 3-PHASE RECEPTACLE(15A)
- ⑪ 3-PHASE RECEPTACLE (30A)




- ① MANUAL & AUTO – START GENERATOR CONTROLLER (DSE 7310MK II)
- ② CONTROL POWER SWITCH
- ③ VOLTAGE REGULATOR
- ④ Circuit Breaker (For main)
- ⑤ EARTH LEAKAGE RELAY
- ⑥ CIRCUIT BREAKER (For 3-Phase Receptacle 32A)
- ⑦ CIRCUIT BREAKER (For 3-Phase Receptacle 63A)
- ⑧ CIRCUIT BREAKER (For 1-Phase Receptacle 16A)
- ⑨ 1-PHASE RECEPTACLE (16A)
- ⑩ 3-PHASE RECEPTACLE(32A)
- ⑪ 3-PHASE RECEPTACLE (63A)

Excellent Maintainability

- Routine maintenance is easy with Denyo's generators. Engine oil, the battery, and coolant are all checked at one location.
- External drain plugs for oil, fuel and water are fitted for convenience in performing routine maintenance.



The filling structure prevents fuel leakage from generator even if spilled while fueling.



Environmentally Friendly

Compliant with the EU's Emission Regulation 2016/1628 (Stage-V).

Environmental Base

An environmental base catches spilled fuel and oil and stop it from leaking out of the generator (accumulated fuel and oil can be discharged through a drain with a single touch).



Easy to drain

Water and oil collected in ECO tank drains easily through large caliber drain valve. Swivel-type oil drain increases the speed of draining compared to conventional type.



Large Caliber



Swivel-type Oil Drain

Safety

- 4 Pole Main Circuit Breakers
- Controller indicates alarm when something is wrong or automatically shuts the engine down.
- Engine shuts down when door opens.
- Emergency stop button.



Exhaust gas after treatment system


DOD DPF:
DCA-41ESEK5, DCA-41USEK5
DPD SCR:
DCA-60ESEI5, DCA-60USEI5, DCA-110ESEI5, DCA-110USEI5



Quiet Operation

Noise comparison (7m/no load) Unit: dB(A)

Denyo's generators run quietly thanks to the Company's original 4 soundproofing technology. The Soundless Type & Ultra Soundproof Type in particular features a low-noise engine, low-noise fan, the addition of a silencer, and special structures such as changes to the hood shape, which create a low noise level similar to that of a quiet office.



Options

- Forklift Pocket Base*1
- Big Tank for 24 hours operation
- Battery Switch
- Customized Color

*About other options, please consult

*1 DCA-60USEI5, DCA-110USEI5 are standard equipment



Engine-Driven Generators

4-Pole Generators | Soundproof Type | Stage V

DCA-14ESEK5



DCA-19ESEY5



DCA-41ESEK5



MODEL		3-PHASE TYPE (Sound Proof Type)			
		DCA-14ESEK5	DCA-19ESEY5	DCA-41ESEK5	
AC Generator					
Frequency	Hz	50			
Output Rating	Prime	kVA	12.5	17.5	37
	Standby	kVA	13.8	19.1	40.7
No. of Phases		3-Phase,4-Wire			
Rated Voltage	V	380 / 400 / 415			
Power Factor		0.8 (Lagging)			
Voltage Regulation	%	Within ± 0.5			
Excitation		Brushless rotating exciter (with AVR)			
Insulation		Class F			
Engine (4-cycle, water-cooled diesel engine)					
Model		KUBOTA D1703M	Yanmar 4TNV88	Kubota V3800	
Type		Swirl chamber type	Swirl chamber Direct injected	Common Rail, Direct injection, cooled EGR, turbocharged	
Rated Output	kW	13.2	16.8	38.9	
Rated Speed	rpm	1500	1500	1500	
No. of Cylinders-Bore x Stroke	mm	3-87 x 92.4	4-88x90	4-100x120	
Displacement	L	1.647	2.189	3.769	
Fuel		ASTM No.2 diesel fuel or equivalent			
Fuel Tank Capacity	L	62	62	110	
Fuel Consumption	L/h	2.8	3.2	6.9	
Lube Oil Capacity	L	7.0	7.4	12.0	
Coolant Capacity	L	5.8	6.0	10.0	
Battery x Quantity		12V-65Ah(80D26R) x1	12V-65Ah(80D26R) x1	12V-70Ah(115D31R) x 1	
Exhaust gas after treatment system		-	-	DOC DPF	
DEF tank capacity (AdBlue tank)			-		
Unit					
Dimensions	Length	mm	1440	1635	2015
	Width	mm	690	750	940
	Height	mm	1080	1210	1670
Dry Weight	kg	585	670	1220	
Sound Power Level					
Sound Power Level	LWA dB	88	87	88	

-Prime output rating applies to operation under standard conditions as per ISO8528-1
 -Standby output rating applies to intermittent or emergency operation for approximately 1 hour as per ISO8528-1.
 - Fuel consumption is based on operation at 75% load.
 -Colors of products would be different from printed ones of catalogues.
 -Specifications given herein are subject to change without notice.

Engine-Driven Generators

4-Pole Generators | Soundproof Type | Stage V

DCA-60ESEI5

DCA-110ESEI5

DCA-165ESEI5



MODEL		3-PHASE TYPE (Sound Proof Type)			
		DCA-60ESEI5	DCA-110ESEI5	DCA-165ESEI5	
AC Generator					
Frequency		50			
Output Rating	Prime	kVA	55	100	150
	Standby	kVA	60	110	165
No. of Phases		3-Phase,4-Wire			
Rated Voltage		V	380 / 400 / 415		
Power Factor		0.8 (Lagging)			
Voltage Regulation		%	Within ± 0.5		
Excitation		Brushless rotating exciter (with AVR)			
Insulation		Class F			
Engine (4-cycle, water-cooled diesel engine)					
Model		Isuzu 4JJ1	Isuzu 4HK1	Isuzu 6HK1	
Type		Common Rail, Inlined, Direct Injected,Turbocharged Aftercooled			
Rated Output		kW	52.9	92.7	133
Rated Speed		rpm	1500	1500	1500
No.of Cylinders-Bore × Stroke		mm	4-95.4×104.9	4-115×125	6-115×125
Displacement		L	2.999	5.193	7.79
Fuel		ASTM No.2 diesel fuel or equivalent			
Fuel Tank Capacity		L	150	250	300
Fuel Consumption		L/h	9.4	16	24.4
Lube Oil Capacity		L	15	23	40.9
Coolant Capacity		L	21	33	41.2
Battery × Quantity			12V-81Ah(115D31R)×1	12V-140Ah(175F51)×1	12V-100Ah(95E41)×2
Exhaust gas after treatment system			DPD SCR	DPD SCR	DPD SCR
DEF tank capacity (AdBlue tank)			28	28	56(28x2)
Unit					
Dimensions	Length	mm	2700	3110	3660
	Width	mm	1060	1300	1450
	Height	mm	1730	1840	2100
Dry Weight		kg	1820	2520	3300
Sound Power Level					
Sound Power Level		LWA dB	93	93	94

-Prime output rating applies to operation under standard conditions as per ISO8528-1
 -Standby output rating applies to intermittent or emergency operation for approximately 1 hour as per ISO8528-1.
 - Fuel consumption is based on operation at 75% load.
 -Colors of products would be different from printed ones of catalogues.
 -Specifications given herein are subject to change without notice.

Engine-Driven Generators

4-Pole Generators | Ultra Soundproof Type Stage V

DCA-18USEY5 DCA-41USEK5 DCA-60USEI5 DCA-110USEI5



MODEL		3-PHASE TYPE (Ultra Sound Proof)				
		DCA-18USEY5	DCA-41USEK5	DCA-60USEI5	DCA-110USEI5	
AC Generator						
Frequency	Hz	50				
Output Rating	Prime kVA	17	37	55	100	
	Standby kVA	17.5	40.7	58.6	110	
No. of Phases		3-Phase,4-Wire				
Rated Voltage	V	380 / 400 / 415				
Power Factor		0.8 (Lagging)				
Voltage Regulation	%	Within ± 0.5				
Excitation		Brushless rotating exciter (with AVR)				
Insulation		Class F				
Engine (4-cycle, water-cooled diesel engine)						
Model		Yanmar 4TNV88	Kubota V3800	Isuzu 4JJ1	Isuzu 4HK1	
Type		Swirl chamber Direct injected	Common Rail, Direct injection, cooled EGR, turbocharged cooled EGR	Common Rail, Inlined, Direct Injected, Turbocharged Aftercooled		
Rated Output	kW	17.2	38.9	51.8	92.7	
Rated Speed	rpm	1500	1500	1500	1500	
No. of Cylinders-Bore x Stroke	mm	4-88x90	4-100x120	4-95.4x104.9	4-115x125	
Displacement	L	2.189	3.769	2.999	5.193	
Fuel		ASTM No.2 diesel fuel or equivalent				
Fuel Tank Capacity	L	92	170	150	300	
Fuel Consumption	L/h	3.1	7.0	9.4	16	
Lube Oil Capacity	L	7.4	13.25	15	23	
Coolant Capacity	L	6.7	9.4	21	33	
Battery x Quantity		12V-65Ah(80D26R) x 1	12V-81Ah(115D31R) x 1	12V-81Ah(115D31R) x 1	12V-140Ah(175F51) x 1	
Exhaust gas after treatment system		-	DOC DPF	DPD SCR	DPD SCR	
DEF tank capacity (AdBlue tank) L		-	-	28	28	
Unit						
Dimensions	Length	mm	1635	2150	2800	3300
	Width	mm	860	1060	1260	1500
	Height	mm	1337	1550	1920	2250
Dry Weight	kg	765	1370	2220	3520	
Sound Power Level						
Sound Power Level	LWA dB	82	84	87	88	

-Prime output rating applies to operation under standard conditions as per ISO8528-1

-Standby output rating applies to intermittent or emergency operation for approximately 1 hour as per ISO8528-1.

- Fuel consumption is based on operation at 75% load.

-Colors of products would be different from printed ones of catalogues.

-Specifications given herein are subject to change without notice.

Engine-Driven Generators

2-Pole Generators

| Soundproof Type | Stage V

DA-6100SSEK5



MODEL			1-PHASE TYPE (2-POLE)
			DA-6000SSEK5
AC Generator			
Frequency	Hz		50
Output Rating	Prime	kVA	5.5
	Standby	kVA	6.1
No. of Phases			1-Phase,4-Wire
Rated Voltage	V		220
Power Factor			1.0
Voltage Regulation	%		Within ± 6.0
Excitation			Brushless rotating exciter
Insulation			Class F
Engine (4-cycle, water-cooled diesel engine)			
Model			Kubota Z482
Type			Swiri chamber type
Rated Output	kW		6.5
Rated Speed	rpm		3000
No.of Cylinders-Bore \times Stroke	mm		2-67 \times 68
Displacement	L		0.479
Fuel			ASTM No.2 diesel fuel or equivalent
Fuel Tank Capacity	L		25
Fuel Consumption	L/h		1.8
Lube Oil Capacity	L		2.5
Coolant Capacity	L		2.75
Battery \times Quantity			12V-45Ah(38B20R) \times 1
Unit			
Dimensions	Length	mm	1140
	Width	mm	650
	Height	mm	795
Dry Weight	kg		240
Sound Power Level			
Sound Power Level	LWA dB		88

-Prime output rating applies to operation under standard conditions as per ISO8528-1

-Standby output rating applies to intermittent or emergency operation for approximately 1 hour as per ISO8528-1.

-Fuel consumption is based on operation at 75% load.

-Colors of products would be different from printed ones of catalogues.

-Specifications given herein are subject to change without notice.

Engine-Driven Welder

Praised for their stable welding performance with little reduction in voltage as a result of their durability and drooping characteristic, Denyo's engine-driven welders are found in use in countries throughout the world. They can even be used as high-performance engine-driven generators. Equipped with idle-control systems that reduce fuel consumption, Denyo's welders provide excellent economic efficiency.

Exceptional Welding Performance


A built-in high-performance generator ensures a stable supply of welding current. This enables outstanding welding performance with an extremely long arc and little arc interruption with the welding electrode.

Welding mode selector switch

Change "Welding mode selector switch" to DROOP/CC to get suitable welding conditions.

DROOP (Drooping characteristic): For stick welding and if you want to change the conditions by the arc length.

CC (Constant Current characteristic): For stick welding and if you want to do stable welding.



CC(Constant current characteristic)
Even when the arc length becomes long and thus the voltage rises, the current remains same.

DROOP(Drooping characteristic)
When the arc length becomes long and thus the voltage rises, the current decreases.


Arc Force Regulator

Adjust "Arc Force Regulator" SOFT, HARD or STANDARD".

SOFT: Pipe welding and welding in all types of positions. Able to get the end result looks more manicured because of the less spatter.

HARD: Overlay welding, Underwater welding, Arc air gouging. Makes arc start easier. (Prevent the electrode form getting stuck on the base material.)

STANDARD: Fillet welding. If you are ever in doubt, choose "STANDARD".



Dual Operator Welding

DLW-400E5W5 can be used for welding by two operators at the same time. This helps reduce purchasing costs for welding machines and contributes significantly to work efficiency improvements.

e-mode (3 Position)

Automatically adjust the engine rpm based on welding current.

Able to do double-duty at all kinds of work sites. Denyo Engine Welders can provide high quality electricity. It can be used for the power source for the precision machinery such as computer.

Safety

- Equipped with an earth leakage relay
- A warning lamp notifies users when an abnormality has occurred (drop in oil pressure, rise in water temperature, poor battery charge).

Maintainability

DLW-400E5W5 provides "one-side maintenance" in which daily checks and maintenance can be performed just by opening a single door.



Environmentally Friendly

Equipped with environmentally friendly clean engines, DLW-400E5W5 complies with the EU's emission regulations (Stage V).

ECO-BASE:

ECO-BASE is a base which has an oil receiver installed inside. You do not need to put an extra tray on the bottom of generator. It is designed to receive fuel, oil and coolant water when they are discharged accidentally.



Engine-Driven Welder

Soundproof Type Stage V

DLW-400ESEW5



MODEL		DLW-400ESEW5
DC Welding Output		
Rated Output	kW	11.9
Rated Current	A	Single: 350 / Dual: 175
Rated Voltage	V	Single: 34.0 / Dual: 27.0
Current Range	A	Single: 60-380 / Dual: 30-190
Rated Duty Cycle	%	75
Applicable Electrode	mm	Single: 2.0-8.0 / Dual: 2.0-4.0
3-Phase AC Power Output		
Rated Output	kVA	15.0
Rated Voltage	V	380
Rated Current	A	22.8
Frequency	Hz	50
Power Factor		0.8
Rating		Continuous
1-Phase AC Power Output		
Rated Output	kVA	6.6 (3.3 x 2)
Rated Voltage	V	220
Rated Current	A	15 x 2
Frequency	Hz	50
Power Factor		1
Rating		Continuous
Engine (4-cycle, water-cooled diesel engine)		
Model		Kubota D1105
Type		Vertical, 4-cycle, water-cooled diesel engine, swirl chamber type
Rated Output	kW	18.0
Rated Speed	min ⁻¹	3000
No. of Cylinders-Bore x Stroke	mm	3-78 x 78.4
Displacement	L	1.123
Fuel		ASTM No.2 diesel fuel or equivalent
Fuel Tank Capacity	L	42
Fuel Consumption	L/h	4.94
Lube Oil Capacity	L	5.1
Coolant Capacity	L	4.7
Battery x Quantity		12V-45Ah x 1 (55B24L)
Dimensions, Weight and Sound Power		
Dimensions Length x Width x Height	mm	1570 x 720 x 870
Dry Weight	kg	523
Sound Power Level	LWA dB	92

- Rated welding load at rated duty cycle. e-mode data is calculated by rated duty cycle at full-range operation.

Our Global Network

Denyo's products are valued by customers around the world and employed in diverse settings. In addition to its locations in Japan, Denyo operates a highly responsive global manufacturing and sales system with three overseas production sites (in Indonesia, the United States, and Vietnam) and four sales and after-sales service sites (in the United States, Singapore, Vietnam and the Netherlands).

1 Denyo Europe B.V.
 Naamrijk 1, 3454 PX De Meern,
 The Netherlands



2 Denyo America Corporation
 1450 Minor Road, Danville,
 Kentucky, 40422 U.S.A
Denyo Manufacturing Corporation
 1450 Minor Road, Danville,
 Kentucky, 40422 U.S.A



3 Denyo Vietnam Co., Ltd.
 Plot A3, Thang Long Industrial Park II,
 Lieu Xa Commune, Yen My District,
 Hung Yen Province, Vietnam



4 Denyo Trading Vietnam Co., Ltd.
 Room 606.03, 6th Floor, Indochina Plaza
 Hanoi Tower, No. 241 Xuan Thuy Street,
 Dich Vong Hau Ward,
 Cau Giay District, Hanoi City, Vietnam

5

Denyo Asia Pte. Ltd.

NO.9 NEYTHAL ROAD SINGAPORE 628614

Denyo United Machinery Pte. Ltd.

NO.9 NEYTHAL ROAD SINGAPORE 628614



Vietnam

3&4

Singapore

5

6

Indonesia



6

P.T. Dein Prima GeneratorJL. Raya Bekasi Km.28, Medan Satria,
Bekasi 17132 Jawa Barat, Indonesia

Company Outline



Denyo Head Office



Fukui Plant

Company Name	Denyo Co., Ltd.
Representative	Takanori Yoshinaga, President
Established	July 2, 1948
Head Office	2-8-5, Nihonbashi-horidomecho, Chuo-ku, Tokyo 103-8566, Japan
Paid-in Capital	¥1,954 million
Fiscal Year-End	March 31
Plants	Fukui and Shiga Prefectures, Japan
Business Lines	Manufacture and sales of engine-driven generators, welders, air compressors and other special machinery

Domestic Denyo Group Companies

Denyo Kosan Co.,Ltd.

2-8-5, Nihonbashi-horidomecho, Chuo-ku,
Tokyo 103-8566, Japan

Nishihatsu Co.,Ltd.

639-1, Chichika,Karatsu,Saga,847-0831,Japan

New Japan Machinery Corporation

3-6-5, Shinyokohamna, Kohoku-ku, Yokohama,
Kanagawa 222-0033, Japan



Naamrijk 1, 3454 PX De Meern, The Netherlands

Tel: +31-30-666-8314 Fax: +31-30-662-2150

<https://www.denyo.co.jp/group/europe>



<http://www.denyo.co.jp/English>

Head Office | 2-8-5, Nihonbashi-horidomecho, Chuo-ku, Tokyo 103-8566, Japan
Tel: +81-3-6861-0055 Fax: +81-3-6861-1188



Printed in Japan 20250115-01